

PRODUCT

INFORMATION



PRATT & LAMBERT PAINTS

SUPRIME®

Interior Alkyd Wall & Trim Primer

S1011 / D1011

DESCRIPTION:

SUPRIME Interior Alkyd Wall & Trim Primer is a high quality, high solids alkyd primer formulated to promote superior performance from interior paints and enamels on wood and plaster surfaces. SUPRIME Interior Alkyd Wall & Trim Primer offers superior adhesion to plaster and wood, provides tannin stain blocking, excellent sealing and hiding, a high film build and easy sanding.

USES:

Use SUPRIME Interior Alkyd Wall & Trim Primer for priming interior new or previously painted surfaces such as doors, window frames, paneling, baseboards, crown molding and other decorative trim work where an enamel paint will be applied.

SIZES: Gallons, Quarts

COLORS:

White - For best finished appearance, tint to approximate color of finish coat. Use approximately 1/4 of topcoat formula, not to exceed 2 ounces of colorant per gallon.

RECOMMENDED SYSTEMS:

NEW WORK:

WOOD

1 coat of SUPRIME Interior Alkyd Wall & Trim Primer
1 or 2 coats P&L Exterior Latex¹ or Alkyd finish

PLASTER

New

Use 1 coat of SUPRIME Int/Ext 100% Acrylic Multi-Purpose Primer instead of SUPRIME Interior Alkyd Wall & Trim Primer

1 or 2 coats of P&L Interior Latex or Alkyd finish

Old (>60 days)

1 coat SUPRIME Interior Alkyd Wall & Trim Primer
1 or 2 coats of P&L Interior Latex¹ or Alkyd finish

FLOORS (Light Duty)

1 coat of SUPRIME Interior Alkyd Wall & Trim Primer
1 or 2 coats of WithSTAND Latex Floor Enamel

REPAINT:

1 coat of SUPRIME Interior Alkyd Wall & Trim Primer
1 or 2 coats P&L Exterior Latex¹ or Alkyd finish

¹If using latex topcoat, scuff sand prime coat before topcoat application.

PRODUCT DETAIL:

| | |
|-----------------------------|---|
| Vehicle: | Alkyd |
| Sheen: | Eggshell (18-28 @ 60°) |
| % Solids: | By Weight: 76% By Volume: 56% |
| Wt./Gallon: | 12.0 lbs. |
| Viscosity: | 89-96 Ku |
| Flashpoint: | 105°F |
| VOC Level: | Max 350g/l (2.92 lbs./gal.) |
| Thinner*: | Mineral Spirits |
| Cleanup: | Mineral Spirits |
| Dry Time: | @ 77°F (25°C) 50% RH: To Touch: 4.0 Hours To Recoat: 18.0 Hours |
| Rec. Film Thickness: | Dry: 2.2 Mils Wet: 4.0 Mils |
| Coverage: | 400 sq. ft./gallon |

APPLICATION:

| | |
|-----------------------|---|
| Brush: | Natural bristle |
| Roller: | 3/8" nap lambswool cover |
| Pad: | Standard |
| Conv. Spray: | Thin with up to 1 pint mineral spirits* |
| Airless Spray: | At package consistency |

Limitations: DO NOT apply when air, surface or product temperature is below 50°F (10°C) or if temperatures might drop to this level within 4 hours after application. DO NOT paint when precipitation is imminent or very late in the day when dew is likely.

*** Do not reduce in municipalities, counties, states or provinces where solvent addition will cause VOC limits to be exceeded. Follow all manufacturer's guidelines when working with solvents.**

Technical Information Line:
1-800-BUY-PRAT (1-800-289-7728)
www.prattandlambert.com

SURFACE PREPARATION:

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

General

Remove all surface contamination by washing with appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.

Wood

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

Plaster

Bare plaster must be cured and hard. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Caulking

Fill gaps between windows, doors, trim, and other through-wall openings with latex or siliconized latex caulk after priming the surface.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

CLEANUP INFORMATION:

Clean spills and spatters immediately with mineral spirits. Clean tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using all solvents.



PRATT & LAMBERT PAINTS

APPLICATION:

Do not apply at air or surface temperatures below 50°F or when air or surface temperatures may drop below 50°F within 48 hours.

Brush

Use a natural bristle brush.

Roller

Use a 3/8" nap lambswool roller cover.

Spray—Airless

Pressure 2000 psi

Tip015 - .019

Spray—Conventional

*Thin with up to 1 pint of mineral spirits**

Air Pressure 40-60 psi

Fluid Pressure 10-20 psi

Cap/Tip 704/FX

TIPS TO IMPROVE

PERFORMANCE:

- Clean the surface thoroughly.
- Prepare the substrate to create a uniform surface.
- Patch cracks, crevices, and through-wall openings using proper sealant or patch.
- Fill voids and openings around windows and doors using proper sealant or patch.
- Caulk as needed using quality latex or siliconized latex caulk or sealant.

CAUTIONS:

For interior use only.

Not for use on horizontal surfaces (roofs, decks, etc.) or where water will collect.

Do not use over zinc or galvanized surfaces.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.