

PRODUCT

INFORMATION



PRATT & LAMBERT PAINTS

PRO-HIDE® Silver Interior Lacquer Undercoater S8005

DESCRIPTION:

A high quality lacquer product formulated for interior use as a primer or surfacer for new wood. It can also be used as a finish coat where a flat final appearance is desired. This product is also recommended to cover or fill grain on wood surfaces. PRO-HIDE Silver Interior Lacquer Undercoater is fast drying, easy sanding, and improves gloss holdout of topcoats.

USES:

Recommended for sealing bare wood trim, moldings, doors, cabinets and woodwork.

SIZES: Fives, Gallons

COLORS:

White. May be tinted with up to 2 oz. of colorant per gallon using 844 colorants.

RECOMMENDED SYSTEMS:

NEW WORK:

WOOD

1 coat PRO-HIDE Silver Interior Lacquer Undercoater
1 or 2 coats desired Lacquer, Alkyd or Latex Finish

REPAINT:

WOOD

Ensure surface to be coated is compatible with lacquer finishes, or remove old finish entirely prior to application.

1 coat PRO-HIDE Silver Interior Lacquer Undercoater
1 or 2 coats desired Lacquer, Alkyd or Latex Finish

PRODUCT DETAIL:

Vehicle:	Lacquer
Sheen:	Flat (Max. 20 @ 85°)
% Solids:	By Weight: 46% By Volume: 24%
Wt./Gallon:	9.1 lbs.
Flashpoint:	21°F PMCC
VOC Level:	610 g/l
Thinner*:	Lacquer Thinner
Cleanup:	Lacquer Thinner
Dry Time:	@ 77°F (25°C) 50% RH: To Touch: 5-10 Minutes Recoat: 0.5 Hour Sand: 20-30 Minutes
Rec. Film Thickness:	Dry: 1.0 Mil Wet: 4.0 Mills
Coverage:	384 sq. ft./gallon @ 1.0 Mil dry film

APPLICATION:

Airless Spray: Tip .013"-.015", 1400 PSI
(reduce with lacquer thinner)

Limitations: DO NOT apply when air, surface or product temperature is below 50°F (10°C) or if temperatures might drop to this level within 4 hours after application. Do not use over metals. Stir reduced material routinely throughout the job. If the product is unused for 8 hours it needs to be remixed thoroughly.

*** Do not reduce in municipalities, counties, states or provinces where solvent addition will cause VOC limits to be exceeded. Follow all manufacturer's guidelines when working with solvents.**

Technical Information Line:
1-800-BUY-PRAT (1-800-289-7728)
www.prattandlambert.com

SURFACE PREPARATION:

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

General

Remove all surface contamination by washing with appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.

Wood

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface. Ensure caulking or patching is compatible with topcoats to be applied before using.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

CLEANUP INFORMATION:

Clean spills and splatters immediately with lacquer thinner. Clean hands and tools immediately after use with lacquer thinner followed by soap and warm water. Flush spray equipment with lacquer thinner and follow with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using these solvents.



PRATT & LAMBERT PAINTS

APPLICATION:

Apply at temperatures above 50°F.
No reduction necessary.

Brush

Not recommended

Roller

Not recommended

Spray-Airless

Pressure 1400 psi

Tip013 - .015

Spray-Conventional

*Thin with up to 1 pint of lacquer thinner**

Air Pressure 40 psi

Fluid Pressure 15 psi

Cap/Tip 704/FF

TIPS TO IMPROVE

PERFORMANCE:

- Clean the surface thoroughly.
- Prepare the substrate to create a uniform surface.
- Patch cracks, crevices, and through-wall openings using proper sealant or patch.
- Fill voids and openings around window and doors using proper sealant or patch.
- Caulk as needed using quality latex or siliconized latex caulk or sealant.

MAINTENANCE:

To assure maximum washability and durability, wait at least two weeks before washing the dry paint film. When removing stains, dirt, and marks, use a soft cloth or sponge with water or other general purpose household cleaner. Penetrating stains and marks can be removed either by applying a solution of household bleach in water and then rinsing with clean water; or, by carefully using an abrasive cleaner and water.

CAUTIONS:

For interior use only.

Not for use on horizontal surfaces (floors, roofs, decks, etc.) or where water will collect.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.