

# PRODUCT

---

## INFORMATION



PRATT & LAMBERT PAINTS

### PRO-HIDE® Gold Exterior Alkyd Wood Primer S8461 / D8461

#### DESCRIPTION:

A high quality, alkyd primer formulated to promote excellent performance from house and trim paints on wood surfaces. PRO-HIDE Gold Exterior Alkyd Wood Primer offers superior adhesion to wood, tannin stain blocking, excellent sealing and hiding, mildew resistance and it provides a tight moisture barrier.

#### USES:

Recommended for priming new or previously painted exterior wood surfaces such as siding, shakes, shingles, fencing, window frames, railings and trim. Also an excellent primer for sealing composition and hardboard siding.

**SIZES:** Gallons, Quarts

#### COLORS:

White - For best finished appearance, tint to approximate color of house paint. See label for tinting guidelines. Use approximately 1/4 of the house paint formula, not to exceed 2 oz.

#### RECOMMENDED SYSTEMS:

##### NEW WORK:

##### NEW WOOD

Spot prime knots with SUPRIME Int/Ext Odorless Stain Blocker  
1 coat of PRO-HIDE Gold Exterior Alkyd Wood Primer to entire surface  
1 or 2 coats of P&L latex or alkyd house paint

##### HARDBOARD/COMPOSITION BOARD

1 coat of PRO-HIDE Gold Exterior Alkyd Wood Primer to entire surface, including sides  
1 or 2 coats of P&L latex or alkyd house paint

##### REPAINT:

Spot prime bare areas with PRO-HIDE Gold Exterior Alkyd Wood Primer  
1 or 2 coats of P&L latex or alkyd house paint

#### PRODUCT DETAIL:

<b>Vehicle:</b>	Alkyd
<b>Sheen:</b>	Flat (0-18 @ 60°)
<b>% Solids:</b>	By Weight: 75.3% By Volume: 57.3%
<b>Wt./Gallon:</b>	11.25 lbs.
<b>Flashpoint:</b>	105°F
<b>VOC Level:</b>	Max 333 g/l (2.71 lbs./gal.)
<b>Thinner*:</b>	Mineral Spirits
<b>Cleanup:</b>	Mineral Spirits
<b>Dry Time:</b>	@ 77°F (25°C) 50% RH: To Touch: 3.0 Hours To Recoat: 24.0 Hours
<b>Rec. Film Thickness:</b>	Dry: 2.3 Mils Wet: 4.0 Mils
<b>Coverage:</b>	400 sq. ft./gallon

#### APPLICATION:

<b>Brush:</b>	Natural Bristle
<b>Roller:</b>	3/8" nap cover
<b>Pad:</b>	Standard
<b>Conv. Spray:</b>	At package consistency
<b>Airless Spray:</b>	At package consistency

**Limitations:** DO NOT apply when air, surface or product temperature is below 50°F (10°C) or if temperatures might drop to this level within 4 hours after application. DO NOT paint when precipitation is imminent or very late in the day when dew is likely.

**\* Do not reduce in municipalities, counties, states or provinces where solvent addition will cause VOC limits to be exceeded. Follow all manufacturer's guidelines when working with solvents.**

Technical Information Line:  
1-800-BUY-PRAT (1-800-289-7728)  
[www.prattandlambert.com](http://www.prattandlambert.com)

## SURFACE PREPARATION:

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### General

Remove all surface contamination by washing with appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.

### Wood and Composition Board

PRO-HIDE Gold Exterior Alkyd Wood Primer can be used on woods that present potential tannin bleeding, such as redwood and cedar. Care must be taken to determine if tannins present in the wood will be activated by the solvent in the coating. To test for bleeding, coat a 4-foot-square section of the surface to be primed with the coating. If no bleeding is evident within 4 hours, proceed with complete priming. If tannin staining occurs, use SUPRIME Int/Ext 100% Acrylic Multi-Purpose Primer.

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Spot prime knots and sap streaks with SUPRIME Int/Ext Odorless Stain Blocker, if needed.

### Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting.

Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

### Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with quality latex or siliconized latex caulk after priming the surface.

## CLEANUP INFORMATION:

Clean spills and spatters immediately with mineral spirits. Clean tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using all solvents.



## PRATT & LAMBERT PAINTS

## APPLICATION:

Do not apply at air or surface temperatures below 50°F or when air or surface temperatures may drop below 45°F within 48 hours. Lower temperature may adversely affect the drying and recoat times. If low temperatures are experienced throughout the application and drying period, extend the recoat/topcoat time to 48 hours.

Do not reduce.

### Brush

Use a natural bristle brush.

### Roller

Use a 3/8" - 3/4" nap synthetic or lambswool roller cover.

### Spray-Airless

Pressure ..... 2000 psi

Tip ..... .017 - .021

### Spray-Conventional

Air Pressure ..... 40-60 psi

Fluid Pressure ..... 15-20 psi

Cap/Tip ..... 704/FX

## TIPS TO IMPROVE

### PERFORMANCE:

- Clean the surface thoroughly.
- Prepare the substrate to create a uniform surface.
- Patch cracks, crevices, and through-wall openings using proper sealant or patch.
- Fill voids and openings around windows and doors using proper sealant or patch.
- Caulk as needed using quality latex or siliconized latex caulk or sealant.

### CAUTIONS:

For exterior use only.  
Not for use on roofs, floors, or decks.  
Not for use on horizontal surfaces where water will collect.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.