

# PRODUCT

## INFORMATION



PRATT & LAMBERT PAINTS

### PRO-HIDE® Silver

### Interior/Exterior Latex Block Filler

Z8485 / F8485

#### DESCRIPTION:

Pro-Hide Silver® Interior/Exterior Latex Block Filler is a high hiding, high solids, easy-to-use formulation that primes and fills interior and exterior above grade, unpainted aggregate block, poured-in-place concrete, precast concrete surfaces, and rough masonry in one application. Not for use over existing coatings.

#### USES:

Recommended for use on interior and exterior aggregate block and concrete surfaces. Schools, Jails, Hospitals, Commercial Buildings

#### SIZES:

Fives

#### COLORS:

White - Tinting is not recommended.

#### RECOMMENDED SYSTEMS:

#### NEW WORK:

1 coat of Pro-Hide Silver® Interior/Exterior Latex Block Filler

Note: Follow with squeegee, trowel or roller, being careful to force material into pores to produce a relatively smooth surface.

Topcoat with 1 or 2 coats of recommended Pratt & Lambert coating.

#### PRODUCT DETAIL:

Vehicle:	100% Acrylic
Sheen:	Flat
% Solids:	By Weight: 72% By Volume: 53%
Wt./Gallon:	14.1 lbs.
Flashpoint:	499°F
VOC Level:	43 g/l (0.36 lbs./gal.)
Thinner:	Water
Cleanup:	Soap and water
Dry Time:	@ 77°F (25°C) 50% RH: To Touch: 1hour Recoat: 18.0 hours for water-borne coatings Recoat: 48 hours for Solvent coatings
Coverage:	50-80 sq. ft./gallon

#### APPLICATION:

Brush:	Nylon or Polyester
Roller:	1/2" nap cover
Pad:	Not recommended
Conv. Spray:	Thin with up to 1 pint water
Airless Spray:	At package consistency

**Limitations:** Do not use in immersion service. Do not apply when air, surface or product temperature is below 5°F (10°C) or if temperatures might drop below these levels within 4 hours after application. Not intended for use as a waterproofer. Do not apply to surface temperatures below 50°. DO NOT USE ON FLOORS.

#### Technical Information Line:

1-800-BUY-PRAT (1-800-289-7728)  
[www.prattandlambert.com](http://www.prattandlambert.com)

## SURFACE PREPARATION:

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### General

Remove all surface contamination by washing with appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with Pratt & Lambert SUPRIME® Int/Ext 100% Acrylic Multi-Purpose Primer.

### Masonry, Concrete, Cement, Block, Stucco, Brick

Allow new surfaces to cure according to supplier's recommendations; at least 30 days. Remove all surface contamination (dirt, dust, grease, oil, peeling paint, heavy chalk, efflorescence, laitance, concrete dust, etc.) by washing with an appropriate cleaner; if necessary, pressure wash with a minimum of 2100 psi, rinse thoroughly and allow to dry. Remove all form release and curing agents. On tilt-up and poured-in-place concrete, commercial detergents or sandblasting may be necessary to remove sealers, release compounds, and to provide an anchor pattern. Repair or replace damaged or defective substrates as needed. Allow brick to age for 1 year prior to coating.

### Plaster

Bare plaster must be cured and hard. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

### Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

### Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

## CLEANUP INFORMATION:

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.



## PRATT & LAMBERT PAINTS

### APPLICATION:

Apply at temperatures above 50°F.  
No reduction necessary.

#### Brush

Use a nylon/polyester brush.

#### Roller

Use a 3/8" - 3/4" nap synthetic roller cover.

#### Spray—Airless

Pressure ..... 2000 psi  
Tip ..... .023 - .031  
Filter ..... 30 mesh

### TIPS TO IMPROVE PERFORMANCE:

- Clean the surface thoroughly.
- Prepare the substrate to create a uniform surface.
- Patch cracks, crevices, and through-wall openings using proper sealant or patch.
- Fill voids and openings around window and doors using proper sealant or patch.
- Caulk as needed using quality latex or siliconized latex caulk or sealant.

### MAINTENANCE:

To assure maximum washability and durability, wait at least two weeks before washing the dry paint film. When removing stains, dirt, and marks, use a soft cloth or sponge with water or other general purpose household cleaner. Penetrating stains and marks can be removed either by applying a solution of household bleach in water and then rinsing with clean water; or, by carefully using an abrasive cleaner and water.

### CAUTIONS:

Protect from freezing.  
Not for use on horizontal surfaces (floors, roofs, decks, etc.) or where water will collect.