

# PRODUCT

---

## INFORMATION



PRATT & LAMBERT PAINTS

### PRO-HIDE® Gold Interior Alkyd Satin Enamel D9100 Series

#### DESCRIPTION:

PRO-HIDE Gold Interior Alkyd Satin Enamel is a high quality, high hiding finish formulated for easy brushing, excellent flow and leveling, and extreme durability and washability.

#### USES:

Recommended for interior new or previously painted wood surfaces such as doors, windows & window frames, paneling, crown moldings or other decorative trim work where a satin enamel finish is desired.

**SIZES:** Fives, Gallons

**COLORS:** Super One Coat White, All Base 1, Base 2 and Base 3 Colors.

#### RECOMMENDED SYSTEMS:

##### NEW WORK:

##### WALLBOARD, PLASTER

1 coat PRO-HIDE Gold Interior Oil Primer  
1 or 2 coats of PRO-HIDE Gold Alkyd Satin Enamel  
New plaster (<60 days) prime with SUPRIME Int/Ext 100% Acrylic Multi-Purpose Primer  
Old plaster (>60 days) prime with PRO-HIDE Gold Interior Oil Primer

##### WOOD

1 coat of PRO-HIDE Gold Interior Oil Primer  
1 or 2 coats of PRO-HIDE Gold Alkyd Satin Enamel

##### METAL

1 coat Tech-gard Alkyd Metal Primer or Tech-gard Acrylic Prime or Finish  
1 or 2 coats of PRO-HIDE Gold Alkyd Satin Enamel

##### MASONRY OR AGGREGATE BLOCK

1 coat PRO-HIDE Gold Latex Primer  
1 or 2 coats of PRO-HIDE Gold Alkyd Satin Enamel  
(For a filled effect, use PRO-HIDE Silver Heavy Duty Latex Block Filler as a first coat)

##### REPAINT:

Spot prime all bare spots with proper primer for the substrate to be coated  
1 or 2 coats of PRO-HIDE Gold Alkyd Satin Enamel

#### PRODUCT DETAIL:

<b>Vehicle:</b>	Alkyd
<b>Sheen:</b>	Satin (35-45 @ 60°)
<b>% Solids:</b>	By Weight: 72% By Volume: 52%
<b>Wt./Gallon:</b>	12.1 lbs.
<b>Flashpoint:</b>	40° (105°F)
<b>VOC Level:</b>	Max 380 g/l (2.91 lbs./gal.)
<b>Thinner*:</b>	Mineral Spirits
<b>Cleanup:</b>	Mineral Spirits
<b>Dry Time:</b>	@ 25°C (77°F) 50% RH: To Touch: 7.0 Hours Recoat: 15.0 Hours Use: 15.0 Hours
<b>Rec. Film Thickness:</b>	Dry: 2.0 Mils Wet: 4.0 Mils
<b>Coverage:</b>	400 sq. ft./gallon

#### APPLICATION:

<b>Brush:</b>	Natural Bristle
<b>Roller:</b>	3/8" lambswool cover
<b>Pad:</b>	Standard
<b>Conv. Spray:</b>	Thin with up to 1 pint Mineral Spirits*
<b>Airless Spray:</b>	At package consistency

**Limitations:** This product will yellow in the absence of light as do all oils.

**\* Do not reduce in municipalities, counties, states or provinces where solvent addition will cause VOC limits to be exceeded. Follow all manufacturer's guidelines when working with solvents.**

Technical Information Line:  
1-800-BUY-PRAT (1-800-289-7728)  
[www.prattandlambert.com](http://www.prattandlambert.com)

## SURFACE PREPARATION:

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### General

Remove all surface contamination by washing with appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with Pratt & Lambert SUPRIME Int/Ext 100% Acrylic Multi-Purpose Primer.

### Plaster

Bare plaster must be cured and hard. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

### Wood

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

### Aluminum and Galvanized Steel

Wash with appropriate cleaner to remove any oil, grease, or other surface contamination. Remove all corrosion with sandpaper, steel wool, or other abrading method.

### Steel

Remove rust and mill scale using sandpaper, steel wool, or other abrading method. Prime bare steel the same day as cleaned.

### Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

### Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

## CLEANUP INFORMATION:

Clean spills and splatters immediately with mineral spirits. Clean tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using all solvents.



## PRATT & LAMBERT PAINTS

### APPLICATION:

Apply at temperatures above 10°C (50°F). No reduction necessary.

#### Brush

Use a natural bristle brush.

#### Roller

Use a 3/8" lambswool roller cover.

#### Spray-Airless

Pressure ..... 2000 psi

Tip ..... .015 - .019

#### Spray-Conventional

*Thin with up to 1 pint of mineral spirits\**

Air Pressure ..... 40-60 psi

Fluid Pressure ..... 10-20 psi

Cap/Tip ..... 704/FX

### TIPS TO IMPROVE

#### PERFORMANCE:

- Clean the surface thoroughly.
- Prepare the substrate to create a uniform surface.
- Patch cracks, crevices, and through-wall openings using proper sealant or patch.
- Fill voids and openings around windows and doors using proper sealant or patch.
- Caulk as needed using quality latex or siliconized latex caulk or sealant.

#### MAINTENANCE:

To assure maximum washability and durability, wait at least two weeks before washing the dry paint film. When removing stains, dirt, and marks, use a soft cloth or sponge with water or other general purpose household cleaner. Penetrating stains and marks can be removed either by applying a solution of household bleach in water and then rinsing with clean water; or, by carefully using an abrasive cleaner and water.

#### CAUTIONS:

For interior use only.

Protect from freezing.

Do not shake excessively.

Not for use on horizontal surfaces (floors, roofs, decks, etc.) or where water will collect.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.